

COLT 600

SCALPING SCREEN

TECHNICAL
SPECIFICATION



PLEASE ENSURE YOU ARE USING ADOBE ACROBAT
READER TO VIEW THIS DOCUMENT.

OVERVIEW

1

HOPPER

- 3.0m³ (3.9 yd³) Hopper Capacity
- 1000mm (40") wide
- Variable speed

2

SCREEN

- 2.34m x 1.17m (8' x 4') Double deck screen
- Variable stroke
- Fixed screen angle
- Wide range of screen media
- Top Deck - Bofor Deck, Fingers, Punch Plate, 3D Punch Plate & Mesh
- Bottom Deck - Mesh & Fingers
- Rubber screen blanket (optional)

3

CONVEYORS

- 650mm (26") Wide fines conveyor with 2.9m (9'6") discharge
- 650mm (26") Wide midgrade conveyor with 2.8m (9'2") discharge
- 1000mm 40" Wide oversize conveyor with 2.7m (8'10") discharge
- Ability to convert to 2 way split

4

ENGINE OPTIONS

- Tier 3: Deutz D2011 L041 - 36.4kW (48.8 Hp) @ 2300 RPM.
- Tier 4F / Stage IV: Deutz TD2.9L4 - 42kW (56 Hp) @ 1900 RPM
- Simple to operate

5

CONTROL SYSTEM

- Simple intuitive operation



VARIABLE SPEED ON
FEEDER, MIDGRADE
AND OVERSIZE AS
STANDARD



UP TO
280
TONNES PER HOUR
(308 US TPH)

FEEDER

**Heavy duty belt feeder,
high torque gearbox and
motor drive:**

- 1000mm (40") wide 4 ply Plain belt
- Variable speed control
- Supergrip drive drum standard



HOPPER

3m³ (3.9 yd³) hopper mounted on heavy duty belt feeder including:


- Folding rear hopper door for direct feeding
- 3.18m (10'5") feed-in height



SCREENBOX

Heavy Duty 2.34m x 1.17m (8' x 4') Double deck screen providing:

- Aggressive performance to tackle most rugged applications.
- A comprehensive variety of media options (mesh, punch plate, finger tines, 3D punch plate, bofors and Screen blanket to control material progress at steeper screening angles.
- Fixed screen angle: 14 degrees
- Side tensioned top and end tensioned bottom deck



CONVEYORS

FINES CONVEYOR

650mm (26") wide fines 3 ply belt which includes:

- Stockpile height 2.9m (9' 6")
- Folding feedboot
- Hydraulically folding
- Variable angle 18 - 25 degrees
- Chevron or Plain belts available



CONVEYORS

MID-GRADE CONVEYOR

**650mm (26") wide mid-grade 3 ply belt
which includes:**

- 2.8m (9' 2") discharge height
- Hydraulically folding
- Chevron or Plain belts available
- Variable Speed control to manage larger pieces or prevent roll-back.
- Variable angle 18 - 25 degrees



CONVEYORS

OVERSIZE CONVEYOR

1000mm (40") wide 3 ply chevron belt featuring:

- 2.7m (8' 10") discharge height
- Impact slips along feedboot
- Hydraulic adjustment for two way split conversion
- Variable Speed control
- Fixed angle 20 degrees



POWER UNIT


User-friendly powerunit including:

- Tier 3: Deutz D2011 L014 - 36.4kW (48.8hp) @ 2300rpm
- Tier 4F/Stage IV: Deutz D2011 TD2.9L4 - 42kW (56hp) @ 1900rpm
- Simple and familiar controls
- Common componentry and service items
- Diesel tank capacity 145ltr (38 US Gal)
- Hydraulic tank capacity 250ltr (66 US Gal)



TRACKS

- Track width 300mm (12")
- Max speed 1.8km/h
- Total flow per track 60LPM
- Dual speed option



OPTIONS

CONVEYOR OPTIONS

- Chevron belt for Fines and mid-fines conveyors
- Conveyor removed – 2 way split
- Hydraulic folding tail conveyor


OTHER OPTIONS

- Quick release wedge screen tensioning system (side tensioned only)
- Telemetry
- Auto lube system
- Crawler track with radio control system, 2V battery charger & mains charger
- Hot / Cold Climate oils
- Screen blanket for material retardation
- Wide range of screen media
- Different coloured machine

WEIGHTS & DIMENSIONS


TRANSPORT

Length: 10.98m (36') **Width:** 2.25m (7' 5") **Height:** 2.55m (8' 4") **Weight:** (standard machine) 12,000kgs (26,455 lbs)




WEIGHTS & DIMENSIONS

WORKING



WEIGHTS & DIMENSIONS

WORKING



GALLERY & MEDIA



200 Coalisland Road,
Dungannon, Co. Tyrone, BT714DR
Tel: +442887718500
Email: evoquip@terex.com



[terex.com/EvoQuip](https://www.terex.com/EvoQuip)

The material in this document is for information only and is subject to change without notice.

Terex assumes no liability resulting from errors or omissions in this document, or from the use of the information contained herein.

Due to continual product development we reserve the right to change specifications without notice.

Photographs are for illustrative purposes only, some or all of the machines in the illustrations may be fitted with optional extras.

Copyright 2019 Terex GB Limited. Published in February 2019.